for safe storage

PRODUCT DATA SHEET

CEMO diesel trolley with submersible pump, 100 L, Automatic dispensing nozzle diesel, 12 V DC, 25 L/min (max.), grey

Order no.: 11102

EAN number: 4052886388280

PRODUCT DESCRIPTION

- certified for transport for direct consumption according to ADR 1.1.3.1 c)
- robust container made from high-quality polyethylene (PE) with handle and grip recess for comfortable handling
- filler neck with integral vents for safe filling
- suction hose with shut-off valve for controlled fuel dispensing
- integral baffle to minimise the movement of liquids during transport
- dispensing nozzle holder directly on the container for safe and handy storage
- self-priming CENTRI SP 30 pump
- puncture-proof all-terrain wheels ø 300 mm
- moulded recess for ratchet straps for securing during transport







TECHNICAL DATA

Content volume	100 l
External dimensions (lxh)	100 x 59 x 43 cm
Weight	20 kg
Use	mobile
Place of installation	Transport
Material	LLDPE
Coating	uncoated
Container colour	grey
Operating voltage	12 V DC
Pump drive	Pump
Max. flow rate	25 L/min (max.)

Dispensing hose length	3.7 m
Hose diameter	DN 19
Stackable	No
ADR instruction	according to ADR 1.1.3.1 c)
Dispensing nozzle	Automatic diesel
Cable length	4
Warranty in years	2
Assembly condition	pre-assembled
Plug	Crocodile clips

SUITABLE STORAGE MEDIA

Diesel
Biodiesel
HVO
Heating oil

LOGISTICS

Package dimensions (l x w x h)	80 x 60 x 115 cm
Units per box	1
Units per pallet	6
Pallet dimensions	120 x 80 x 160 cm
Shipping weight	45 kg
Freight	General cargo
Customs tariff number	84137021

ACCESSORIES



8644 - Digital flow metre K24 (Cematic pumps) for Cematic pumps



10229 - Plug DIN 9680, 3-pin, 6-24 V, max. 25A, IP54



10230 - Socket DIN 9680, 3-pin, 6-24V, max.25A, IP54



12344 -

Link to product

Technical specifications subject to change/Errors and omissions excepted. © CEMO 11102-en 11.26
CEMO GmbH | In den Backenländern 5 | 71384 Weinstadt | Germany | Tel. +4971519636-0 | kontakt@cemo-group.com