Abrasive fibre disc, multibond

FS 966 ACT



Properties

Bonding agent	Resin
Grain	Ceramic Al. oxide
Coating	Close

Materials

Stainless steel	●

Applications

- Stainless steel processing industry
- Apparatus and container manufacturing

Product benefit

Micro-crystalline self-sharpening effect - High aggressiveness throughout the service life - Outstanding grit adhesion - Long service life, especially suitable for heavy duty applications - Increase in performance due to low temperatures - Multibond prevents heat tinting

Available grits:

16 20 24 30 36 40 50 60 80 100 120 150 180 220 240 280 320 360 400 500 600 800 1000 1200 1500 2000 2500 3000

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
115 x 22 X-LOCK	⊛ 50	80	80 m/s	13300 rpm	FS 966	X-LOCK	25	351165
115 x 22 X-LOCK	⊛ 50	40	80 m/s	13300 rpm	FS 966	X-LOCK	25	351166
115 x 22 X-LOCK	⊛ 50	60	80 m/s	13300 rpm	FS 966	X-LOCK	25	351167
115 x 22	⊛ 30	36	80 m/s	13300 rpm	FS 966	star shaped hole	25	316490

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de

Diameter x Hole in mm	Hole pattern	grain	Vmax m/s	Max. RPM	type of coat.abras.	bore shape	Packing unit/pcs.	Cat. number
115 x 22	⊛ 30	40	80 m/s	13300 rpm	FS 966	star shaped hole	25	316491
115 x 22	⊛ 30	60	80 m/s	13300 rpm	FS 966	star shaped hole	25	316492
115 x 22	⊛ 30	80	80 m/s	13300 rpm	FS 966	star shaped hole	25	316493
115 x 22	⊛ 30	50	80 m/s	13300 rpm	FS 966	star shaped hole	25	318504
115 x 22	⊛ 30	120	80 m/s	13300 rpm	FS 966	star shaped hole	25	324237
125 x 22 X-LOCK	⊛ 50	80	80 m/s	12250 rpm	FS 966	X-LOCK	25	351162
125 x 22 X-LOCK	⊛ 50	60	80 m/s	12250 rpm	FS 966	X-LOCK	25	351163
125 x 22 X-LOCK	⊛ 50	40	80 m/s	12250 rpm	FS 966	X-LOCK	25	351164
125 x 22	⊛ 30	36	80 m/s	12250 rpm	FS 966	star shaped hole	25	316494
125 x 22	⊛ 30	40	80 m/s	12250 rpm	FS 966	star shaped hole	25	316495
125 x 22	⊛ 30	60	80 m/s	12250 rpm	FS 966	star shaped hole	25	316496
125 x 22	⊛ 30	80	80 m/s	12250 rpm	FS 966	star shaped hole	25	316497
125 x 22	⊛ 30	24	80 m/s	12250 rpm	FS 966	star shaped hole	25	318305
125 x 22	⊛ 30	120	80 m/s	12250 rpm	FS 966	star shaped hole	25	324239
180 x 22	⊛ 30	36	80 m/s	8500 rpm	FS 966	star shaped hole	25	316498
180 x 22	⊛ 30	40	80 m/s	8500 rpm	FS 966	star shaped hole	25	316499
180 x 22	⊛ 30	60	80 m/s	8500 rpm	FS 966	star shaped hole	25	316501
180 x 22	⊛ 30	80	80 m/s	8500 rpm	FS 966	star shaped hole	25	316502
180 x 22	⊛ 30	24	80 m/s	8500 rpm	FS 966	star shaped hole	25	318352
180 x 22	⊛ 30	120	80 m/s	8500 rpm	FS 966	star shaped hole	25	324238

Klingspor Schleifsysteme GmbH und Co. KG
Hüttenstraße 36 - 35708 Haiger - Germany
Fon + 49 (0) 2773 922-0 Fax + 49 (0) 2773 922-186
sales@klingspor.de - www.klingspor.de