Classic Solutions

STANDARD MAT • INDOOR

WHY CHOOSE THIS MAT?

Classic Solutions mats are specially designed to pick up dirt and moisture in heavy traffic areas and buildings where a high level of cleanliness is critical.

- **ECONYL® regenerated nylon** reduces the global warming impact of nylon by up to 90% compared with the material from oil. ECONYL® is made of **100% Post-consumer recycled** content
- The rubber is **Phthalate free** and consists of **up to 34% post-industrial recycled content** in the rubber polymer to further reduce the impact on the environment
- Solution-dyed nylon fibers for **durable performance** after repeated wash cycles
- High Twist heat set nylon fibers are resistant against **crushing** and allow **dirt** to filter into the mat rather than remaining on top of the carpeted surface
- **The rubber backing** prevents curling and cracking in all types of weather
- Bleach / UV resistant
- The textiles used are **OEKO-TEX® certified**, ensuring they meet stringent standards for safety and environmental responsibility

SPECIFICATIONS

Yarn	**100% ECONYL® regenerated BCF polyamide, twisted & heat set multifilaments** • **Carpet weight**: 722 g/m²
Backing	• **Primary Backing:** Non-woven PET • **Rubber backing**: 100% nitrile rubber with up to 34% post-industrial recycled content in the polymer - phthalate free - For maximum oil resistance, durability, and performance. Compression-molded with reinforced borders on all four sides. • **Thickness:** 1.4 mm
Border	• **Border thickness**: 2.5 mm • **Border width**: 2 cm
Other properties	• **Pile thickness**: 10 mm • **Total weight**: 2397g/m² • **Static Control:** Antistatic behaviour: Approx 10^{11} ohms (ISO 10965) - Personal Charging: <2kV antistatic (ISO6356) • **Flammability:** Cfl-s1
Recommended use	Recommended for indoor commercial use at entryways, in lobbies, at front desks or anywhere additional traction or moisture control is needed.

Size Tolerance: +/- 2%
Weight Tolerance: +/- 5%

STANDARD SIZES

60x85	75x85	85x115	85x150
85x300	115x180	115x200	115x240
115x250	115x300	150x200*	150x240*
150x250*	150x300*	200x200**	200x300**

SPECIAL SIZES

Max. Size: 200 cm x 550 cm

* Dark Grey is the only colour available in widths wider than 150 cm.
* Green Black and Red Black are not available in widths wider than 115cm.

COLOURS

Standard Black/colour

10 Light Grey

20 Slate Grey

30 Dark Brown

50 Dark Grey*

70 Steel Grey

90 Black Mink

150 Green Black

160 Blue Black

180 Light Brown

190 Red Black

Clear colours

107 Clear Black

130 Clear Granite

200 Scarlet

Special patterns

114 Black Granite

104 Pebble Stone

CLEANING INSTRUCTIONS

Classic Solutions mats can be cleaned in several different ways:

1. They can be commercially laundered (see Laundering Instructions)
2. Vacuumed regularly (daily in high-traffic areas; weekly in lower-traffic applications)
3. Cleaned with an extractor and laid flat to dry

Hang to dry. Mats should always be dry before they are placed back in service and cooled before rolling.

Laundering Instructions

1. Flush, 2-3 Min. on a medium water level with a maximum temperature of 49°C
2. Flush (optional), 2-3 Min. on a medium water level with a maximum temperature of 49 °C
3. Break, 2-3 Min. on a high water level with a maximum temperature of 49 °C
4. Rinse, 2 Min. on a high water level with cold temperature
5. Rinse, 2 Min. on a high water level with cold temperature
6. Extract on low speed, 1-2 Min.
7. Shakeout with the drum turning, 1 Min.
8. Extract, on a maximum of 250G, 3-5 Min.
9. Dry (optional), 5-10 Min. with a maximum basket temperature of 82 °C
10. Cooldown, 5 Min.

Additional recommendations

- All Solution Dyed Mats can be washed together.
- For Heavy Soiled Mats, increase the temperature up to max. 71 °C
- The wash or rinse baths should have a pH between 6 and 9.5; use low pH non-ionic detergents.
- Do not overdry mats; Basket-temperature of the dryer should not exceed 82 °C.
- If mats are not dried, the final rinse can be increased to 49 °C. This will reduce moisture retention following extraction.
- Lay mats flat following removal from washer; allow mats to cool before rolling.